



Multi-Position Heating Mantle LD-LMHM-A22

Labodam Equipment Ltd.

info@labodam.com | www.labodam.com

Multi-Position Heating Mantle LD-LMHM-A22

Overview

Multi-Position Heating Mantle LD-LMHM-A22 is a table top device with 4 × 500 ml maximum capacity, offers 4 channel multi-position heating mantle and temperature ranges from RT+20 to 250°C. It offers step less speed adjustment, uniform temperature, fast heating-up, safety and durability. Features anti-corrosion, age-resistant and rotatory knob for setting of temperature and speed on hot plate. It adopts electronic temperature regulation heating mode.

Features:

- Designed with electronic temperature regulation heating mode
- Rotatory knob to set temperature and speed
- Offers 6 channel multi-position heating mantle
- The maximum temperature is up to 450°C
- Equipped with cold rolling sheet stretching and spraying exterior
- Offers step less speed adjustment, uniform temperature, fast heating-up, safety and durability
- Equipped by anti-corrosion, age-resistant, durable and safe
- The stirrer is operated synchronously to provide the same reaction conditions as the sample
- Effectively reduce the speed noise

Applications:

Multi-Position Heating Mantle is used in petrochemical industries, medicine, and environment protection institutions for liquid heating, chemical synthesis, physical and chemical analysis, biopharmaceuticals etc.

Specifications:

Capacity	4 × 500 ml
Net weight	8 kg
Work model	Continuous
Outer shell	Cold rolled steel plate, surface spraying
Gross weight	10 kg
Heating mode	Surface heat conduction
Power supply	200 to 240 V
Heating Power	4 × 0.25 kW
Heating element	Nickel chromium alloy wire
Packing dimension	730 × 220 × 210 mm
Temperature range	RT+20 to 250°C

External dimension	690 × 180 × 180 mm
Surface Max. temperature	450°C